IN THE CLAIMS

Please rewrite Claims 1, 2 and 9 as set forth in 37 C.F.R. § 1.121(c)(1)(i). A copy of all amended claims showing the additions and deletions in accordance with 37 C.F.R. § 1.121(c)(ii) is attached hereto.

- 1 (Amended) A furnace for cracking hydrocarbon feed to produce olefins, said furnace comprising:
 - (a) at least one fired radiant chamber, wherein said radiant chamber is divided into at least two separate independent radiant zones by a fired radiant chamber dividing means;
 - (b) at least one radiant burner in each said zone of said fired radiant chamber;
 - (c) a convection chamber in direct communication with each said fired radiant chamber;
 - (d) at least one independent process coil for each said separate independent radiant zone, wherein each said independent process coil extends through at least a portion of said convection chamber and extends into one of said separate and independent radiant zones before exiting said furnace;
 - (e) a flue for discharging flue gas located at the top of said convection chamber of said furnace, and
 - (f) a means for independently controlling the radiant burner in each said separate independent radiant zone.

- 2. (Amended) A furnace for cracking hydrocarbon feed to produce olefins, said furnace comprising:
 - at least two fired radiant chambers, wherein each said radiant chamber is divided into at least two separate independent radiant zones by a fired radiant chamber dividing means;
 - (b) at least one radiant burner in each of said zones of said fired radiant chambers;
 - (c) a convection chamber in direct communication with each said fired radiant chamber;
 - (d) at least one independent process coil for each said separate independent radiant zone, wherein each said process coil extends through at least a portion of said convection chamber and extends into one of said separate and independent radiant zones before exiting said furnace;
 - (e) a flue for discharging flue gas located at the top of each said convection chamber of said furnace; and
 - (f) a means for independently controlling the radiant burner in each said separate independent radiant zone.
- 9. (Amended) An improved pyrolysis cracking furnace having a radiant cracking chamber wherein said improvement comprises dividing said radiant cracking chamber into at least two separate and independent radiant cracking zones by providing a dividing wall in said radiant cracking chamber to separate said radiant cracking chamber into at least two separate and independent radiant cracking zone, and separately and